

DIGITAL MINI CRANE SCALE



- Aluminum die-casting enclosure
- Fast resolution switching
- Stainless steel shackle and hook
- 20mm(0.8") LCD display
- Fixed hook
- Idle mode to maximize the battery life
- HOLD function
- Tare In / Tare Out
- Unit switch: kg / lb / N
- Auto overload alarm at 100%F.S. +9°
- Auto shutdown function
- Easy to replace battery

Basic Parameters:

- Accuracy Class: OIML Class III
- Display: 20mm(0.8") LCD
- Tare Range: Full capacity
- Safe Overload: 120%Max. Capacity
- Overload Indication: 100%Max. Capacity +9e
- Ultimate Overload: 300%Max. Capacity
- Operation Time: 100 hours
- Operating Temperature: -10 to +40 [15 to 105]
- Operating Humidity: < 85%RH under 20 [68]
- Battery: 3 1.5VAA Battery (included).

OCS-L120

- Brand : **SIMONA**
- Capacity: 120kg
- Graduation: 50g
- Min.Weight: 1000g
- Resolution: 2400
- Temperature Range: -10oC ~ 40oC
- Battery: 1.5VAA x 3

OCS-L300

- Brand : **SIMONA**
- Capacity: 300kg
- Graduation: 100g
- Min.Weight: 2000g
- Resolution: 3000
- Temperature Range: -10oC ~ 40oC
- Battery: 1.5VAA x 3

* Designs and specifications are subject to change for improvement without prior notice