

DIGITAL COUNTING SCALE



Features:

- High Precision Load Cell up to 1/15000 display resolution
- Full digital calibration
- Three LCD display with EL backlight
- Full range tare auto zero tracking
- Low battery and charging status indication
- Power saving facility
- Counting by sample or unit weight setting
- Accumulation memories & Quantity checking
- Build in rechargeable battery
- Multi-functional and high accuracy
- High quality with economic price

HC-1.5

- Brand : **SNOWREX**
- Capacity: 1.5kg
- Readability: 0.1g
- Resolution: 0.01g
- Pan Size(s/s): 265 x 205 mm
- Power: AC Adaptor 9V/500Ma
- Weight: Approx.4 kg
- Environment: 0°C ~ 40°C (32°F ~ 104°F) RH less than 85%

HC-3

- Brand : **SNOWREX**
- Capacity: 3kg
- Readability: 0.2g
- Resolution: 0.02g
- Pan Size(s/s): 265 x 205mm
- Power: AC Adaptor 9V/500Ma
- Weight: Approx.4 kg
- Environment: 0°C ~ 40°C (32°F ~ 104°F) RH less than 85%

HC-7.5

- Brand : **SNOWREX**
- Capacity: 7.5kg
- Readability: 0.5g
- Resolution: 0.05g
- Pan Size(s/s): 265 x 205mm
- Power: AC Adaptor 9V/500Ma
- Weight: Approx.4 kg
- Environment: 0°C ~ 40°C (32°F ~ 104°F) RH less than 85%

HC-15

- Brand : **SNOWREX**
- Capacity: 15kg
- Readability: 1g
- Resolution: 0.1g
- Pan Size(s/s): 265 x 205mm
- Power: AC Adaptor 9V/500Ma
- Weight: Approx.4 kg
- Environment: 0°C ~ 40°C (32°F ~ 104°F) RH less than 85%

HC-30

- Brand : **SNOWREX**
- Capacity: 30kg
- Readability: 2g
- Resolution: 0.2g
- Pan Size(s/s): 265 x 205mm
- Power: AC Adaptor 9V/500Ma
- Weight: Approx.4 kg
- Environment: 0°C ~ 40°C (32°F ~ 104°F) RH less than 85%

* Designs and specifications are subject to change for improvement without prior notice