

SHRINK TUNNEL PACKING MACHINE



Shrinking package machine adopts quartz far-infrared tube in direct heating shrinking Membrane to achieve perfect contraction package. The machine is made reliable by electronic unlimited shift and booster in temperature control. The products packed can be sealed well, preventing from getting damp and against knocks. It is suitable for tight wrapping packaging of many-piece articles and tray package, which is applied in contraction package in food, beverage, candies, stationary, hardware tools, daily necessities and chemical products.

ABS-A400

- Power Supply: 220v 50 ~60Hz
- Power: 7.5KW
- Conveyor Speed: 0 ~ 10m/min
- Conveyor Loading: 5KG
- Size of Shrink Oven: 800 x 400 x 200
- Machine size (mm): 1350 x 720 x 880

ABS-B400

- Power Supply: 220v 50~60Hz
- Power: 7.5KW
- Conveyor Speed: 0 ~ 10m/min
- Conveyor Loading: 5KG
- Size of Shrink Oven: 830 x 400 x 200
- Machine size (mm): 1350 x 790 x 880



ABS-C450

- Power Supply: 380v 50~60Hz
- Power: 8.5KW
- Conveyor Speed: 0 ~ 10m/min
- Conveyor Loading: 5KG
- Size of Shrink Oven: 830 x 450 x 250
- Machine size (mm): 1280 x 760 x 1360

* Designs and specifications are subject to change for improvement without prior notice