


DIGITAL CRANE SCALE



UPW-3000 series

- Brand : **UP GREEN**
- Capacity (kg): 15000
- Graduation (kg): 5
- Dimension (mm) A (Total L): 980
- Dimension (mm) C (Ring W): 135
- Dimension (mm) B (Ring H): 215
- Dimension (mm) G (Hook W): 75
- Dimension (mm) Size (H x L x W): 160 x 320 x 230
- Weight (kg) : 60

UPW-3000 series

- Brand : **UP GREEN**
- Capacity (kg): 20000
- Graduation (kg): 10
- Dimension (mm) A (Total L): 1030
- Dimension (mm) C (Ring W): 135
- Dimension (mm) B (Ring H): 215
- Dimension (mm) G (Hook W): 90
- Dimension (mm) Size (H x L x W): 160 x 320 x 230
- Weight (kg) : 65

UPW-3000 series

- Brand : **UP GREEN**
- Capacity (kg): 30000
- Graduation (kg): 10
- Dimension (mm) A (Total L): 1210
- Dimension (mm) C (Ring W): 140
- Dimension (mm) B (Ring H): 230
- Dimension (mm) G (Hook W): 105
- Dimension (mm) Size (H x L x W): 160 x 320 x 230
- Weight (kg) : 106

Weighing Performance:

- Good dynamic weighing system, weighing result not subject to influence of swaying.
- Auto battery power display when shut on/off.
- High accuracy and high stability because of 1,000,000 internal resolution.
- Auto shut off (prevent of battery loss because of forget to shut off)
- With remote controller, easy to operate.
- Add up, auto add up, tare, remote tare, display hold, resolution choice display, random weigh revising.
- Overload remind display, low battery warning.
- Chroming, smooth and rust proof.

Technology Standards:

- Accuracy : conformity with international III scale standard (GB/T11883-2002).
- Battery Type: Fully sealed lead-acid battery, 6V/4Ah
- Security Overload: 150% FS
- Broken Overload: 300% FS
- Temperature: -10° C ~ 50° C
- Display: 5d 30mm (0.5") high brightness LED
- Battery of remote controller: 23A 12V x 1 battery
- Stability of reading: <5.0S
- Remote control: 10~15m
- Charger: DC12V / 1000mA
- Humidity: <90% R.H.
- Battery Last: 60 Hrs.

* Designs and specifications are subject to change for improvement without prior notice